



NO. 42D ALSO GENERAL DESIGN AND
DIMENSIONS OF NO. 42 TYPE

Each consists of 200 narrow contacts arranged in ten levels. Each level consists of two rows having ten contacts in each row.

Intended for use with No. 197 type switches in Step-by-Step Dial Telephone Systems except No. 42DB which is intended for use in the J92606 Portable No. 1 Traffic Usage Recorder in common systems.

No. 42D, DA & DB: Terminal ends of contacts are tinned.

No. 42E & EA: Terminal ends of contacts are arranged for connection to their associated wires by means of a machine-clinching operation. In addition, the terminal ends of contacts on banks to which the local cable is to be connected are arranged for mechanically wrapped connections.

Furnished only as components of wired multiples of equipment. When necessary to replace individual No. 42E and No. 42EA banks for maintenance purposes, it is intended that the No. 42D and No. 42DA banks, respectively, be used.

Code No.	Comcode	Rating
42D	100 007 020	A.T.&T.Co.Std.
42E	100 007 038	" "
(*)42DA	100 007 046	" "
(a)42DB	100 007 053	" "
(*)42EA	100 007 061	" "

- (*) The No. 42DA and EA are the same as the No. 42D and E, respectively, except that they are provided with a lug for mounting the lower end of a No. 9A commutator.
- (a) The No. 42DB is the same as the No. 42D except that it is provided with a lug for mounting the upper end of a No. 9B commutator.